



## RS280i Rugged Rack Mount 2U server



### Dimensions:

19"W x 20"D x 3.5"H

Weight: ~50 lb. depending on options

- 1 or 2 Xeon up to 3.6 GHz CPU
- Up to 12 GB DDR 333 MHz Memory
- Up to 4 x 73 GB up to 300 GB Removable SCSI Drive – RAID Option Available
- On Board Audio
- 2 PCI-X, 1 X PCI 32 Bit Low profile Expansion Slots
- 1 x PCI Express Low Profile Slot
- PC Health Monitor

- Quality
- Performance
- High availability
- Leading edge
- Rugged
- Windows/Linux OS

- 800 MHz FSB
- Intel 7320 Chipset
- 1-ch 320 SCSI
- Slim Line DVD-RW
- On-board GigE
- USB
- Floppy
- Optional Sony AIT-3 Tape Drive

### Features:

- Corrosion resistant stainless steel chassis w/slides
- Designed to:
  - Mil-901D Grade B
  - Mil-STD 810F shock & Vibe
- Designed to Mil-Std 461D
- Operating temperature: 0-45°C
- Storage temperature: -40-+71°C
- Altitude 10,000 ft. operating, 40,000 ft non-operating
- Humidity 5-95% non-condensing
- Dual redundant 450W Power Supplies